



ELECTRICAL CHARACTERISTICS:  
 CONTACT CURRENT RATING : 1AMPERES.  
 DIELECTRIC WITHSTANDING VOLTAGE : AC 500V P  
 INSULATION RESISTANCE : 500 MΩ MIN AT DC  
 CONTACT RESISTANCE : 30 mΩ MAXI.  
 OPERATING TEMPERATURE : -55°C TO+105°C.

MECHANICAL CHARACTERISTICS:  
 CONTACT INSERTION FORCE :5.0KG MAXIMUM.  
 CONTACT SEPARATION FORCE :3.0KG MINIMUM.

MATERIALS:  
 CONTACT: BRASS.  
 INSULATOR: P.B.T.UL 94V-0 RATED.  
 SHELL: COLD ROLLED STEEL.

FINISHES:  
 CONTACTS :GOLD FLASHED 1U”.

PART NO	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	F±0.25	Maximum insertion force	Minimum pulling force
HDD-26S	39.20	33.32	24.66	7.90	12.55	5.80	6.0	4.0

TOLERANCE				SIGNATURES		DATE
X.	±0.20	X°	±5°	DRAFT: 李国雄	23.8.1	
.X	±0.15	.X°	±2°			
.XX	±0.10	.XX°	±1°		CHECKEO: 周海霞	23.8.1
.XXX	±0.05	.XXX°	±0.5°			



REV	PART NO.& SAMPLE NO.	DATE	BY		APPROVAL:		TITLE	HDDB26P Female, Solder Type
A	<b>41080B</b>			SHEET	SCALE	UNIT		
B				OF	1:1	mm	∅	CUSTOMER