



NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL:ZINC ALLOY
2. IDC MATERIAL:PC
3. PCB MATERIAL:FR-4 T=1.6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE  
STAMP PIN 0.30mm
5. IDC LIFE:200 TIMES MIN
6. WIRE:AWG 23-26

					Material			Item No.	<b>87010G</b>
					Angles Projection			Part Name	FTP CAT6A Field Termination Plug, toolless
					Size			ERP	
					Scale			Part No.	
					Unit				
					A4				
					X:1				
					mm				
					Sheet			Version: A/0	
					1 OF 1				
					Tolerance				
					0.00-20.00 ±0.10				
					20.00-50.00 ±0.15				
					50.00-100.00 ±0.20				
					100.00- ±0.25				
					Angle ±30°				
SYM		Number	Bill No. of Alteration	Signature	Date				
Drawn									
Checked									
Approved									