

ZYCOO



EH60

Network Horn Speaker

Applicable Scenarios



Schools



Industrial Facilities



Plazas



Train/Bus Stations



Warehouses



Playgrounds



Manufacture Facilities



Stadiums



Sports Stadiums



Parks



Scenic Areas



Warehouses

Features

- Built-in 60W amplifier, 380Hz to 6.5KHz frequency range and 133dB max sound pressure level.
- With IP66 protection rating and well thermal durability.
- External power supply (DC 24V 3A).
- Supports 48K OPUS high-quality audio encoding.
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
- Compatible with IP camera VMS via ONVIF.
- Supports three lines SIP accounts, in which users may register the endpoint in more than one system for achieving different functionality purposes.
- Support HTTP API for alarm in transmit.

Specifications

Speaker

Speaker component	1.5"mid-frequency driver unit
Sensitivity	116dB/1m/1W/1KHz
Max sound pressure level	133dB
Amplifier	Class D Amplifier
Rated power	DC: 4Ω 60W
Frequency range	380Hz – 6.5KHz
Coverage Pattern	78°H 78°V(1kHz/-6dB), effective distance 300m
Acoustics	Mono

Specifications

Audio	
Audio codecs	G.722, G.711 A-law, G.711 U-law, Opus
Audio streaming	MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kbps, Mono or Stereo
Interface	
Interface	1x RJ45 1x 3-pin 3.81mm Phoenix terminal (Dry Contacts) 1x2-pin 3.81mm Phoenix terminal (Switch) 1x DC Female interface (5.5*2.1)
Network	
interface	10/100Mbps
Protocols	SIP(RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH
Administration	
Configuration	Web interface or auto provisioning server
Provisioning method	MQTT IoT Protocol
Mechanical Properties	
Memory	128MB RAM, 256MB Flash
Power input	DC 24V-3A
Casing	Aluminum (ADC12)
IP Rating	IP66
Color	White
Weight	3KG
Dimension	Ø325 x 350 mm (12.8 x 13.78 in)
Mouning method	Wall/Pole mounted
Environmental	
Installation environment	Indoor/Outdoor
Operating temperature	-30°C - 70°C(-22°F - 158°F)
Storage temperature	-40°C - 70°C(-40°F - 158°F)
Humidity	10% - 95% RH Non-condensing
Approvals	
Approvals	EN 55032:2015, EN 55035:2017, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 62368-1:2014+A11:2017, FCC Pat 15B ,IP66



zycoo@zycoo.com

www.zycoo.com

© 2025 Zycoo Communications LLC All rights reserved